

SPECIFICATION

DISPLACEMENT	449cc	CURB WEIGHT	208kg
BORE X STROKE	72mm×55.2mm	GROUND CLEARANCE	215mm
COMPRESSION RATIO	11.5:1	FUEL TANK CAPACITY	18.5 Litres
MAX POWER	33KW/8000rpm	DASHBOARD SPEC	5.98 inch TFT Dashboard
MAX TORQUE	42Nm/6500rpm	FRAME	20CrMo High-strength steel pipe
FUEL INJECTION SYSTEM	EFI	SWINGARM	Aluminum Alloy
TOP SPEED	150km/h	ABS	Dual Channel Switchable ABS
COOLING	Water cooling	TIRE SIZE	Front Tire:90/90-21 M/C 54H Rear Tire:140/70 R18 M/C 67H
VALVE MECHANISM	DOHC, 2 cylinders, 8 valves	WHEELS	Tubeless Tire
ENGINE TYPE	Inline-twin cylinders , 4-stroke	FRONT BRAKE	J. Juan brake single disc Ø320mm
EMISSION STANDARD	Euro V+ /EPA	REAR BRAKE	J. Juan brake single disc Ø255mm
L x W x H(mm)	2265mm x855mm x1350mm	FRONT SUSPENSION	KYB fully adjustable suspension, 208mm stroke
WHEELBASE	1525mm	REAR SUSPENSION	Preload & Rebound Adjustable Linkage Suspension
SEAT HEIGHT	850mm	C(color)	Green / White / Black



ZHEJIANG MORINI VEHICLE CO.,LTD
www.motomorini.com

ALTR HIKE





Ferocious power, pull ahead in a flash.
Exclusively for the most hardcore riders

Designed for motorcycle enthusiasts passionate about outdoor exploration,
pursuing freedom and eager to conquer all road conditions.
Be it off-road novice or veteran rider, ALLTRHIKE 450 fulfills your desire for adventure

ALLTRHIKE



Dual Channel Swichable ABS & J.Juan brake Single disc brakes



KYB upside-down absorber



Bag quick release



Handguards



Rear seat with adjustable inclination heated seat (optional)



High position muffler



Center stand



USB TYPE A+C

Displacement
449.5cc

Compression Ratio
11.5:1

Peak Power
33Kw/8000rpm

Peak Torque
42Nm/6500rpm



Adjustable windshield



21-inch Spoke Wheel



High-mounted fender



Plastic belly pan